

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions or listings of claims for this application.

Listing of Claims:

1. (Currently Amended) A micro-lens array, comprising:
a first set of micro-lenses comprising a plurality of first micro-lenses each having a first size; and
a second set of micro-lenses comprising a plurality of second micro-lenses each having a second size;
wherein at least one of said plurality of first micro-lenses at least abuts without overlapping at least one of said plurality of second micro-lenses.
2. (Original) The micro-lens array of claim 1, further comprising a third set of micro-lenses comprising a plurality of third micro-lenses each having a third size.
3. (Original) The micro-lens array of claim 2, wherein said first, second, and third sizes are equal to each other.
4. (Original) The micro-lens array of claim 1, wherein a focal length of each of said plurality of first micro-lenses is approximately equal to a focal length of each of said plurality of second micro-lenses.

5. (Original) The micro-lens array of claim 1, wherein a focal length of each of said plurality of first micro-lenses corresponds to a first wavelength of light, and wherein a focal length of each of said plurality of second micro-lenses corresponds to a second wavelength of light.

6. (Currently Amended) A micro-lens array, comprising:
a first set of micro-lenses comprising a plurality of first micro-lenses;
a second set of micro-lenses comprising a plurality of second micro-lenses;
and
a third set of micro-lenses comprising a plurality of third micro-lenses;
wherein said first micro-lenses at least abut without overlapping said second and third micro-lenses.

7. (Original) The micro-lens array of claim 6, wherein said first micro-lenses have a first size and said second micro-lenses have a second size, said second size being no smaller than said first size.

8. (Original) The micro-lens array of claim 6, wherein said first, second, and third micro-lenses each have approximately a same focal length.

9. (Original) The micro-lens array of claim 6, wherein a focal length of each of said plurality of first micro-lenses corresponds to a first wavelength of light, wherein a

focal length of each of said plurality of second micro-lenses corresponds to a second wavelength of light, and wherein a focal length of each of said plurality of third micro-lenses corresponds to a third wavelength of light.

10. (Original) The micro-lens array of claim 6, wherein a respective one of said second micro-lenses overlaps surrounding ones of said first micro-lenses.

11. (Original) The micro-lens array of claim 6, wherein said first, second and third sizes are equal to each other.

12. (Currently Amended) A micro-lens array, comprising:
a first set of micro-lenses comprising a plurality of first micro-lenses; and
a second set of micro-lenses comprising a plurality of second micro-lenses;
wherein said first micro-lenses exhibit different optical transmission
properties than said second micro-lenses, and
wherein said first micro-lenses abut said second micro-lenses without
overlapping.

13. (Original) The micro-lens array of claim 12, comprising a third set of micro-lenses comprising a plurality of third micro-lenses.

14. (Original) The micro-lens array of claim 13, wherein said third micro-lenses exhibit different optical transmission properties than at least one of said first and second micro-lenses.

15. (Original) The micro-lens array of claim 14, wherein said third micro-lenses exhibit different optical transmission properties than both said first and second micro-lenses.

16. (Original) The micro-lens array of claim 13, wherein said first micro-lenses abut said second and third micro-lenses.

17. (Original) A semiconductor-based imager, comprising:
- a pixel array having embedded pixel cells, each with a photosensor; and
 - a micro-lens array, comprising:
 - a first set of micro-lenses comprising a plurality of first micro-lenses each having a first size; and
 - a second set of micro-lenses comprising a plurality of second micro-lenses each having a second size;
- wherein the micro-lens array is at least approximately space-less between at least one of said plurality of first micro-lenses and at least one of said plurality of second micro-lenses.

18. (Original) The semiconductor-based imager of claim 17, wherein said first size is different than said second size such that pixel cells corresponding to said second micro-lenses receive a greater amount of light than pixel cells corresponding to said first micro-lenses.

19. (Original) The semiconductor-based imager of claim 18, wherein said first micro-lenses correspond to green pixel cells, and wherein said second micro-lenses correspond to red and/or blue pixel cells.

20. (Original) The semiconductor-based imager of claim 17, wherein said micro-lens array further comprises a third set of micro-lenses comprising a plurality of third micro-lenses each having a third size.

21. (Original) The semiconductor-based imager of claim 20, wherein the micro-lens array is at least approximately space-less between said pluralities of first, second, and third micro-lenses.

22. (Original) The semiconductor-based imager of claim 20, wherein a focal length of each of said plurality of first micro-lenses is equal to a focal length of each of said plurality of second micro-lenses and a focal length of each of said plurality of third micro-lenses.

23. (Original) The semiconductor-based imager of claim 20, wherein focal lengths of each of the pluralities of first, second, and third micro-lenses are adjusted for a specific color signal.

24. (Currently Amended) A semiconductor-based imager, comprising:
a substrate having pixel cells formed thereon, each with a photosensor;
and
a micro-lens array for presenting an image for said pixel cells, said micro-lens array comprising:
a first plurality of first micro-lenses each having a first size; and
a second plurality of second micro-lenses each having a second size larger than said first size;
wherein said second micro-lenses are adapted to collect a greater amount of light than said first micro-lenses, and
wherein at least one of said second micro-lenses abuts without overlapping at least one of said first micro-lenses.

25. (Original) The semiconductor-based imager of claim 24, wherein said first and said second micro-lenses each exhibit a similar focal length.

26. (Original) The semiconductor-based imager of claim 25, wherein said focal length extends to said photosensors.

27. (Original) The semiconductor-based imager of claim 24, wherein a focal length of the plurality of first micro-lenses is adjusted for a first color signal, and wherein a focal length of the plurality of second micro-lenses is adjusted for a second color signal.

28. (Cancelled)

29. (Original) The semiconductor-based imager of claim 24, wherein a respective one of said second micro-lenses overlaps surrounding ones of said first micro-lenses

30. (Original) The semiconductor-based imager of claim 24, further comprising a color filter array positioned over said pixel cells.

31. (Currently Amended) The semiconductor-based imager of claim 30, wherein said color filter array is positioned between said micro-lens array and said ~~wafer~~ substrate.

32. (Currently Amended) The semiconductor-based imager of claim 24, further comprising a light shield positioned between said micro-lens array and said ~~wafer~~ substrate.

33. (Original) The semiconductor-based imager of claim 24, wherein said micro-lens array further comprises a third plurality of third micro-lenses each having a third size.

34. (Currently Amended) The semiconductor-based imager of claim 33, wherein said first, ~~second~~, and third sizes are equal.

35. (Original) The semiconductor-based imager of claim 33, wherein at least one of said first micro-lenses abuts at least one of said second micro-lenses and at least one of said third micro-lenses.

36. (Currently Amended) A semiconductor-based imager, comprising:
a substrate having pixel cells formed thereon, each with a photosensor;
and
a micro-lens array for presenting an image for said pixel cells, said micro-lens array comprising:
a first set of micro-lenses comprising a plurality of first
micro-lenses each having a first size; and

a second set of micro-lenses comprising a plurality of second micro-lenses each having a second size no smaller than said first size;

wherein said second micro-lenses are each positioned in a space between adjacent said first micro-lenses such that said second micro-lenses contact without overlapping said first micro-lenses.

37. (Original) The semiconductor-based imager of claim 36, further comprising a color filter array positioned over said pixel cells.

38. (Original) The semiconductor-based imager of claim 37, wherein said color filter array is positioned between said micro-lens array and said ~~wafer~~ substrate.

39. (Original) The semiconductor-based imager of claim 36, wherein said second size is larger than said first size.

40. (Original) The semiconductor-based imager of claim 36, wherein said first and said second micro-lenses each exhibit a similar focal length.

41. (Original) The semiconductor-based imager of claim 40, wherein said focal length extends to said photosensors.

42. (Original) The semiconductor-based imager of claim 36, wherein a focal length of the plurality of first micro-lenses is adjusted for a first color signal, and wherein a focal length of the plurality of second micro-lenses is adjusted for a second color signal.

43. (Original) The semiconductor-based imager of claim 36, wherein a respective one of said second micro-lenses overlaps surrounding ones of said first micro-lenses.

44. (Original) The semiconductor-based imager of claim 36, wherein said micro-lens array further comprises a third plurality of third micro-lenses each having a third size.

45. (Original) The semiconductor-based imager of claim 44, wherein said first, second, and third sizes are equal.

Claims 46-55 (Canceled).

56. (New) The semiconductor-based imager of claim 33, wherein said second and third sizes are equal.